

Pressure regulator MS6N-LR

FESTO



Characteristics


At a glance

Very compact series for use close to the process directly on the machine

- Grid dimension: 62 mm
- Good control characteristics with minimal pressure hysteresis and primary pressure compensation
- Return flow option for exhausting from output 2 to input 1 already integrated
- High flow rate with minimal pressure drop
- Optional pressure sensor

Ordering data - modular system


Link [ms6n-lr](#)



Configurable product

This product and all its product options can be ordered online via the configurator.

Function



- For stepless, precise adjustment of the required operating pressure
- The pressure regulator keeps the working pressure largely constant, irrespective of compressed air fluctuations in the network and due to air consumption

Pneumatic connection

By installing connecting plates it is easier to replace the module if necessary (e.g. when using piping).

Pressure regulation range

Four pressure regulation ranges:

- 0.3 ... 4 bar
- 0.3 ... 7 bar
- 0.5 ... 12 bar
- 0.5 ... 16 bar

Pressure gauge alternatives

Two pressure gauge connections for variable installation

Alternative pressure gauge scale

The scaling of the built-in pressure gauge can be selected. The unit options available are [MPa], [bar] / [psi].


Secondary exhausting

The regulated working pressure can also be reduced without a consuming device via the optional secondary exhausting.


Rotary knob alternative

Optionally with longer rotary knob or with pressure gauge integrated in the rotary knob.

[LD] Long rotary knob




[DM1] Rotary knob pressure gauge, small




Characteristics

[DM2] Rotary knob pressure gauge, large




Alternative mounting position

[] None



Rotary knob positioned above the appliance as standard.

[KD] Rotary knob underneath




Optionally with rotary knob positioned below the device.


Lockability

Various options for locking the rotary knob to protect the settings from being changed.

[AS] Can be locked using accessories



[E11] With integrated lock



Type of mounting

[WR] Mounting bracket with knurled nut on regulator knob



- For wall mounting an individual device
- Not compatible with devices that have a pressure gauge with rotary knob and long rotary knob

[WP] Mounting bracket basic design



- For connecting the modules for wall mounting
- In combination with connecting plate MS6-AQ... for mounting an individual device on a wall
- In combination with mounting plate MS6-AEND for wall mounting of a single device
- Same wall distance when used in combination with series MS4 and MS6

Characteristics

[WPM]

Mounting bracket for hooking in service unit components



- For connecting the modules for wall mounting
- In combination with connecting plate MS6-AQ... for mounting an individual device on a wall
- In combination with mounting plate MS6-AEND for wall mounting of a single device
- For installing modules with the regulator knob pointing downwards

[WB]

Mounting centrally at rear (wall mounting top and bottom), connecting plates not required



- For wall mounting an individual device

Flow direction

Available with flow in the opposite direction.

Type code

001	Series	
MS	MS series	
002	Size	
6	Grid dimension 62 mm	
003	Thread type	
N	NPT thread	
004	Function	
LR	Pressure regulator	
005	Pneumatic connection, inch	
1/4	Female thread NPT 1/4	
3/8	Female thread NPT 3/8	
1/2	Female thread NPT 1/2	
AQN	Sub-base NPT1/4	
AQP	Sub-base NPT3/8	
AQR	Sub-base NPT1/2	
AQS	Sub-base NPT3/4	
006	Pressure regulation range	
D5	0.3 ... 4 bar	
D6	0.3 ... 7 bar	
D7	0.5 ... 12 bar	
D8	0.5 ... 16 bar	
007	Pressure gauge alternatives	
	None	
A4	Adapter for EN pressure gauge 1/4, without pressure gauge	
AD1	Pressure sensor with LCD display, M8 plug, PNP, 3-pin	
AD2	Pressure sensor with LCD display, M8 plug, NPN, 3-pin	
AD3	Pressure sensor with LCD display, M12 plug, PNP, 4-pin, analogue output 4 ... 20 mA	
AD4	Pressure sensor with LCD display, M12 plug, NPN, 4-pin, analogue output 4 ... 20 mA	
AD7	Pressure sensor with switching display, M8 plug, threshold value comparator, PNP, N/O	
AD8	Pressure sensor with switching display, M8 plug, threshold value comparator, PNP, N/C	
AD9	Pressure sensor with switching display, M8 plug, window comparator, PNP, N/O	
AD10	Pressure sensor with operational status indicator, M8 plug, window comparator, PNP, N/C	
RG	Integrated pressure gauge, red/green scale	
VS	Cover plate	

008	Alternative pressure gauge scale	
	MS pressure gauge	
BAR	bar	
MPA	MPa	
009	Secondary exhausting	
	With secondary exhausting	
OS	Without secondary exhaust	
010	Rotary knob alternative	
	None	
LD	Long rotary knob	
DM2	Rotary knob pressure gauge, large	
011	Alternative mounting position	
	None	
KD	Rotary knob underneath	
012	Lockability	
	None	
AS	Can be locked using accessories	
E11	With integrated lock	
013	Type of mounting	
	Without mounting bracket	
WB	Mounting centrally at rear (wall mounting top and bottom), connecting plates not required	
WP	Mounting bracket basic design	
WPM	Mounting bracket for hooking in service unit components	
WR	Mounting bracket with knurled nut on regulator knob	
014	Flow direction	
	Flow direction from left to right	
Z	Flow direction from right to left	

Datasheet

General technical data

Pressure regulation range	0.5 ... 12 bar			0.3 ... 4 bar			0.3 ... 7 bar			
Pneumatic connection, port 1	1/4 NPT	3/8 NPT	1/2 NPT	1/4 NPT	3/8 NPT	1/2 NPT	1/4 NPT	3/8 NPT	1/2 NPT	3/4 NPT
Pneumatic connection, port 2	1/4 NPT	3/8 NPT	1/2 NPT	1/4 NPT	3/8 NPT	1/2 NPT	1/4 NPT	3/8 NPT	1/2 NPT	3/4 NPT
Size	6									
Design	Pressure regulator with pressure gauge									
Controller function	Output pressure constant, Via primary pressure compensation, With secondary venting									
Type of mounting	Either: Front panel mounting In-line installation With accessories									
Mounting position	optional									
Actuator lock	Rotary knob with detent, can be closed with accessories									Rotary knob with detent
Max. pressure hysteresis	0.25 bar									
Pressure gauge (ANALOG) or Pressure display (DIGITAL)	With pressure gauge									

Standard nominal flow rate q_n

Pressure range/actuation	0.3 ... 4 bar, manually actuated [D5]			0.3 ... 7 bar, manually actuated [D6]				0.5 ... 12 bar, manually actuated [D7]		
Pneumatic connection, port 1	1/4 NPT	3/8 NPT	1/2 NPT	1/4 NPT	3/8 NPT	1/2 NPT	3/4 NPT	1/4 NPT	3/8 NPT	1/2 NPT
Standard nominal flow rate (standardised to DIN 1343)	2,400 l/min	5,500 l/min	7,500 l/min	3,000 l/min	5,800 l/min	6,500 l/min		2,700 l/min	4,500 l/min	5,500 l/min

Operating and environmental conditions




Operating pressure	0.8 ... 20 bar
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4], Inert gas
Note on operating and pilot medium	Lubricated operation possible (in which case lubricated operation will always be required)
Ambient temperature	-10 ... 60°C
Media temperature	-10 ... 60°C
Storage temperature	-10 ... 60°C
Corrosion resistance class CRC ¹⁾	2 - Moderate corrosion stress
Suitable for use with food ²⁾	See supplementary material information

1) More information www.festo.com/x/topic/crc2) More information www.festo.com/catalogue/ms-lr → Support/Downloads.

Materials

Material housing	Die-cast aluminium
Material membrane	NBR
Material seals	NBR
Note on materials	RoHS-compliant
LABS (PWIS) conformity	VDMA24364-B1/B2-L


Datasheet

Standard flow rate q_n as a function of output pressure p_2 ($p_1 = 147$ psi) – MS6N-LR-1/4Link [2271](#)Standard flow rate q_n as a function of output pressure p_2 ($p_1 = 147$ psi) – MS6N-LR-3/8Link [2273](#)Standard flow rate q_n as a function of output pressure p_2 ($p_1 = 147$ psi) – MS6N-LR-1/2Link [2275](#)

Dimensions

Dimensions – Basic type Integrated MS pressure gauge with standard scale/
with red-green scale

Download CAD data www.festo.com




	B1	B2	B3		D1	D2	L1	L2	L3	L4
	[inch]	[inch]	1) [inch]	RG [inch]		[inch]	[inch]	[inch]	[inch]	[inch]
MS6N-LR-1/4	2,44	1,22	3,03	3,09	1/4 NPT	2,02	3,70	1,54	3,74	3,35
MS6N-LR-3/8					3/8 NPT					
MS6N-LR-1/2					1/2 NPT					

1) Standard scale

Dimensions

Dimensions – Alternative mounting position, rotary knob underneath

Download CAD data www.festo.com




	B1	B2	1)	B3	D1	D2	L1	L2	L3	L4
	[inch]	[inch]	[inch]	RG [inch]		[inch]	[inch]	[inch]	[inch]	[inch]
MS6N-LR-1/4-...-KD	2,44	1,22	3,03	3,09	1/4 NPT	2,02	3,70	1,54	3,74	3,35
MS6N-LR-3/8-...-KD					3/8 NPT					
MS6N-LR-1/2-...-KD					1/2 NPT					

1) Standard scale

Dimensions

Dimensions – Pressure gauge alternatives, cover plate Download CAD data www.festo.com




	B2 [inch]	B3 [inch]	D1
MS6N-LR-1/4-...-VS	1,22	2,99	1/4 NPT
MS6N-LR-3/8-...-VS			3/8 NPT
MS6N-LR-1/2-...-VS			1/2 NPT

Dimensions

Dimensions – Pressure gauge alternatives, adapter for EN pressure gauge


Download CAD data www.festo.com



	B2 [inch]	B3 [inch]	D1	D4
MS6N-LR-1/4-...-A4	31	78,5	1/4 NPT	1/4 NPT
MS6N-LR-3/8-...-A4			3/8 NPT	
MS6N-LR-1/2-...-A4			1/2 NPT	

Dimensions

Dimensions – Pressure gauge alternatives, AD7 ... 10 pressure sensor without LCD display (only switching indicator) www.festo.com




	B2 [inch]	B3 [inch]	B5 [inch]	B6 [inch]	D6
MS6N-...-AD7, AD8, AD9, AD10	1,22	3,11	~2,00	0,63	M8x1

Dimensions

Dimensions – Pressure gauge alternatives, AD11/AD12 pressure sensor with LCD display


Download CAD data www.festo.com



	B2 [inch]	B3 [inch]	B4 [inch]	B5 [inch]	B6 [inch]	D6	L5 [inch]	L6 [inch]
MS6N-...-AD11	1,22	4,01	3,69	2,01	1,26	M12x1	1,62	1,54
MS6N-...-AD12						M8x1	1,49	

Dimensions

Dimensions – Pneumatic connection, AQ... Sub-base Download CAD data www.festo.com




	B1 [inch]	B2 [inch]	B3 [inch]	B4 [inch]	B5 [inch]	D1	D2 [inch]	L1 [inch]	L2 [inch]	⌀ 1 [inch]
MS6N-LR-...-AQN	4,53	1,04	0,81	1,22	3,87	1/4-18 NPT	0,94	2,44	0,61	34
MS6N-LR-...-AQP						3/8-18 NPT				
MS6N-LR-...-AQR						1/2-14 NPT				
MS6N-LR-...-AQS						3/4-14 NPT				

Dimensions

Dimensions – Type of mounting, WB mounting bracket


Download CAD data www.festo.com



	B1 [inch]	B2 [inch]	B3 [inch]	B4 [inch]	L1 [inch]	L2 [inch]	L3 [inch]	L4 [inch]
MS6-WB	3,13	2,44	0,18	2,12	6,20	2,80	0,26	2,80

Dimensions

Dimensions – Type of mounting, WR mounting bracket Download CAD data www.festo.com




	B1 [inch]	B2 [inch]	B3 [inch]	B4 [inch]	L1 [inch]	L2 [inch]	L3 [inch]
MS6-WR	2,76	1,65	0,32	1,57	2,64	2,24	0,28

Dimensions

Dimensions – Type of mounting, WP mounting bracket


Download CAD data www.festo.com



	B1 [inch]	B2 [inch]	B3 [inch]	B4 [inch]	B5 [inch]	L1 [inch]	L2 [inch]	L3 [inch]	L4 [inch]
MS6-WP	3,11	2,44	0,18	2,13	4,53	6,22	2,80	0,26	2,80

Dimensions

Dimensions – Type of mounting, WPM mounting bracket Download CAD data www.festo.com




	B1 [inch]	B2 [inch]	B3 [inch]	B4 [inch]	B5 [inch]	L1 [inch]	L2 [inch]	L3 [inch]	L4 [inch]
MS6-WPM	3,90	2,72	0,69	2,13	5,08	3,88	1,63	0,26	1,63

Dimensions

Dimensions – Rotary knob with latch

Download CAD data www.festo.com




[1] Max. panel thickness

	D2 [inch]	D3	L3 [inch]	L8 [inch]	L9 [inch]
MS6N-LR-...	2,02	M44x1	3,39	0,83	0,55

Dimensions


Dimensions – Rotary knob with latch, can be locked using accessories Download CAD data www.festo.com



	B4 [inch]	B5 [inch]	D2 [inch]	D3	L3 [inch]	L8 [inch]	L9 [inch]
MS6N-LR-....AS	2,53	1,53	2,02	M44x1	3,74	0,47	0,20

Dimensions

Dimensions – Rotary knob with integrated lock


[Download CAD data](#) www.festo.com


- [1] Max. panel thickness
[2] Installation dimension

	D2 [inch]	D3	L3 [inch]	L8 [inch]	L9 [inch]	L10 [inch]
MS6N-LR-...-E11	2,02	M44x1	4,33	0,83	0,55	2,36

Dimensions

Dimensions – Rotary knob, long, with latch Download CAD data www.festo.com




	D2 [inch]	L3 [inch]	L10 [inch]
MS6N-LF-...-LD	2,02	3,39	5,47

Dimensions

Dimensions – Rotary knob, long, with latch, can be locked using accessories

Download CAD data www.festo.com




[1] For pressure setting: fully pull out telescopic knob

	B4 [inch]	B5 [inch]	D2 [inch]	L3 [inch]	L10 [inch]
MS6N-LR-...-LD-AS	2,54	1,53	2,02	3,76	5,85

Dimensions


Dimensions – Rotary knob pressure gauge, large Download CAD data www.festo.com



	D2 [inch]	D3	L3 [inch]	L4 [inch]	L8 [inch]	L9 [inch]
MS6N-LR-...-DM2	2,01	M44x1	3,31	3,70	1,00	0,72


Ordering data

Ordering data					
	Pneumatic connection, port 1	Pressure regulation range	Product weight	Part no.	Type
	1/4 NPT	0.3 ... 4 bar	730 g	531442	MS6N-LR-1/4-D5-AS
		0.3 ... 7 bar		531448	MS6N-LR-1/4-D6-AS
		0.5 ... 12 bar		531454	MS6N-LR-1/4-D7-AS
	3/8 NPT	0.3 ... 4 bar		531444	MS6N-LR-3/8-D5-AS
		0.3 ... 7 bar		531450	MS6N-LR-3/8-D6-AS
		0.5 ... 12 bar		531453	MS6N-LR-3/8-D6-AS-Z
				531459	MS6N-LR-3/8-D7-AS-Z
				531456	MS6N-LR-3/8-D7-AS
	1/2 NPT	0.3 ... 4 bar		531443	MS6N-LR-1/2-D5-AS
		0.3 ... 7 bar		531449	MS6N-LR-1/2-D6-AS
		0.5 ... 12 bar		531458	MS6N-LR-1/2-D7-AS-Z
			531455	MS6N-LR-1/2-D7-AS	
	3/4 NPT	0.3 ... 7 bar	1,030 g	8233004	MS6N-LR-AQS-D6

Ordering information – Modular product system			
	Short type code	Part no.	Type
	MS6N-LR	527664	MS6N-LR

Peripherals


Peripherals overview



Accessories		→ Link
Type/order code	Description	
[1] Pressure regulator MS6N-LR	Illustration based on MS4-LR as an example	ms6n-lr
[2] Mounting bracket MS6-WB	Order code [WR]; for single device	27
[3] Mounting bracket MS4-WBM	Not available for this size	-
[4] Mounting bracket MS6-WR	Order code [WR]; for single device	27
[5] Knurled nut MS-LR	For single device (included in the scope of delivery)	ms6n-lr
[6] Padlock LRVS-D		29
[7] Cover cap MS6-END	For devices without connecting plate	29
[8] Module connector MS6-MV1	For device combinations and individual devices with connecting plate	27
[9] Connecting plate SET MS6-AQ...	Order code [AQ...]; for device combinations	29
[10] Pressure sensor AD11/AD12	Order code [AD11], [AD12]; pressure sensor SPAU with LCD display	spau
[11] Connecting cable NEBU-M8...-LE4/NEBU-M12...-LE4		28
[12] Pressure sensor AD7 ... AD10	Order code [AD7], [AD8], [AD9], [AD10]; pressure sensor SDE5 with switching indicator	sde5
[13] Connecting cable NEBU-M8...-LE3		28
[14] Adapter for EN pressure gauge 1/4	Order code [A4]	ms6n-lr
[15] Pressure gauge MA		28
[16] Cover plate VS	Order code [VS]	ms6n-lr

Accessories

Module connector MS6-MV1						
	Size	Material module connector	LABS (PWIS) conformity	Product weight	Part no.	Type
	6	POM, High-alloy stainless steel	VDMA24364-B1/B2-L	33 g	8119204	MS6-MV1

Mounting bracket MS6-WP...						
	Size	Material bracket	LABS (PWIS) conformity	Product weight	Part no.	Type
	6	Die-cast aluminium	VDMA24364-B1/B2-L		1025936	MS6-WPE
				76 g	532195	MS6-WP
				115 g	526074	MS6-WPB
				144 g	526073	MS6-WPM-D
				154 g	532186	MS6-WPM-2D

Mounting bracket MS6-WB						
	Size	Material bracket	LABS (PWIS) conformity	Product weight	Part no.	Type
	6	Steel	VDMA24364-B1/B2-L	121 g	532196	MS6-WB

Mounting bracket MS6-WR						
	Size	Material bracket	LABS (PWIS) conformity	Product weight	Part no.	Type
	6	Steel	VDMA24364-B1/B2-L	90 g	526075	MS6-WR

Accessories

Pressure sensor SPAU-...-T

	Pneumatic connection	Electrical connection 1, connector system	LABS (PWIS) conformity	Product weight	Part no.	Type
	R1/8	M12x1, A-coded to EN 61076-2-101	VDMA24364-B1/B2-L	70 g	8001206	SPAU-P10R-T-R18M-L-PNLK-PNVBA-M12D
		M8x1, A-coded, to EN 61076-2-104			8001203	SPAU-P10R-T-R18M-L-PNLK-PNVBA-M8D
	R1/4	M12x1, A-coded to EN 61076-2-101			8001208	SPAU-P10R-T-R14M-L-PNLK-PNVBA-M12D
		M8x1, A-coded, to EN 61076-2-104			8001209	SPAU-P10R-T-R14M-L-PNLK-PNVBA-M8D

Connecting cables NEBA, straight

Connecting cables NEBA, straight						
	Electrical connection 1, connector system	Electrical connection 2, connector system	Electrical connection 2, number of connections/ cores	Cable length	Part no.	Type
	M12x1, A-coded to EN 61076-2-101	Open end	4	2.5 m	8078239	NEBA-M12G5-U-2.5-N-LE4
				5 m	8078240	NEBA-M12G5-U-5-N-LE4
			5	2.5 m	8078242	NEBA-M12G5-U-2.5-N-LE5
				5 m	8078243	NEBA-M12G5-U-5-N-LE5
	M8x1, A-coded, to EN 61076-2-104		3	2.5 m	8078223	NEBA-M8G3-U-2.5-N-LE3
				5 m	8078224	NEBA-M8G3-U-5-N-LE3
			4	2.5 m	8078227	NEBA-M8G4-U-2.5-N-LE4

Connecting cables NEBA, angled

Connecting cables NEBA, angled						
	Electrical connection 1, connector system	Electrical connection 2, connector system	Electrical connection 2, number of connections/ cores	Cable length	Part no.	Type
	M12x1, A-coded to EN 61076-2-101	Open end	4	2.5 m	8078248	NEBA-M12W5-U-2.5-N-LE4
				5 m	8078249	NEBA-M12W5-U-5-N-LE4
	M8x1, A-coded, to EN 61076-2-104		3	2.5 m	8078230	NEBA-M8W3-U-2.5-N-LE3
				5 m	8078231	NEBA-M8W3-U-5-N-LE3
			4	2.5 m	8078233	NEBA-M8W4-U-2.5-N-LE4

Pressure gauge MA

	Conforms to standard	Pneumatic connection	LABS (PWIS) conformity	Product weight	Part no.	Type
	EN 837-1	G1/4	VDMA24364-B1/ B2-L	70 g	183901	MA-40-16-G1/4-EN
		R1/8		60 g	525726	MA-40-16-R1/8-E-RG
		R1/4		70 g	187080	MA-40-16-R1/4-EN
				75 g	525729	MA-50-16-R1/4-E-RG

Accessories

Cover cap MS6-END						
	Size	Material housing	LABS (PWIS) conformity	Part no.	Type	
	6	PA-reinforced	VDMA24364-B1/B2-L	538780	MS6-END	

Mounting plate MS6-AEND						
	Size	Material housing	LABS (PWIS) conformity	Product weight	Part no.	Type
	6	PA-reinforced	VDMA24364-B1/B2-L	11.1 g	535408	MS6-AEND1

Connecting plate SET MS6-A...						
	Size	Pneumatic connection, port 1	Material sub-base	Product weight	Part no.	Type
	6	1/4 NPT	Die-cast aluminium	300 g	526076	MS6N-AQN
		3/8 NPT			526077	MS6N-AQP
		1/2 NPT			526078	MS6N-AQR
		3/4 NPT			526079	MS6N-AQS

Nut MS...-WRS						
	Size	Material nut	LABS (PWIS) conformity	Product weight	Part no.	Type
	6	Wrought aluminium alloy	VDMA24364-B1/B2-L	20.9 g	532188	MS6-WRS

Padlock LRVS-D						
	LABS (PWIS) conformity		Product weight	Part no.	Type	
	VDMA24364-B1/B2-L		120 g	193786	LRVS-D	